


Protection
Circuit protection

CE CB CCC TÜV Rheinland



TOMC3-63 Miniature Circuit Breaker (Curve B, C, D)



IEC 60947-2

AS/NZS 60898.1

IEC 60898-1

EN 60898-1

■ TOMC3-63 circuit breakers are multi-standard circuit breakers which combine the following functions:

- Circuit protection against short-circuit currents,
- Circuit protection against overload currents,
- Suitable for industrial isolation according to IEC/EN 60947-2, standard.

Main

Product or component type	Miniature circuit-breaker
Device application	Distribution
Poles description	2P
Number of protected poles	2
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B, C, D
Breaking capacity	4.5kA


Complementary

[Ue] rated operational voltage	230V/240V, 380V/415V AC	
Control type	Toggle	
Local signalling	ON/OFF indication	
Mounting mode	Clip-on	
Mounting support	DIN rail 35mm	
Colour	Grey	
Endurance (O-C)	Electrical	10,000 cycles
	Mechanical durability	20,000 cycles


Environment

Standards	IEC 60947-2, IEC 60898-1, EN60898-1, AS/NZS 60898.1	
IP degree of protection	IP40 for modular enclosure conforming to IEC 60529	
	IP20 conforming to IEC 60529	
Operating altitude	2000 m	
Ambient air temperature for operation	-35°C to +70°C	
Ambient air temperature for storage	-40°C to +85°C	

Connection

Rating	Tightening torque	Copper cables	
		Rigid	Flexible or ferrule
			
1 to 25 A 32 to 63 A	2 N.m 2.5 N.m	1 to 25 mm² 1 to 35 mm²	1 to 16 mm² 1 to 25 mm²

Catalog numbers

Type	Width 9 mm modules			
2P	Rating (In)	B Curve	C Curve	D Curve
	1A	TOMC3-63/2/B1	TOMC3-63/2/C1	TOMC3-63/2/D1
	3A	TOMC3-63/2/B3	TOMC3-63/2/C3	TOMC3-63/2/D3
	5A	TOMC3-63/2/B5	TOMC3-63/2/C5	TOMC3-63/2/D5
	6A	TOMC3-63/2/B6	TOMC3-63/2/C6	TOMC3-63/2/D6
	10A	TOMC3-63/2/B10	TOMC3-63/2/C10	TOMC3-63/2/D10
	16A	TOMC3-63/2/B16	TOMC3-63/2/C16	TOMC3-63/2/D16
	20A	TOMC3-63/2/B20	TOMC3-63/2/C20	TOMC3-63/2/D20
	25A	TOMC3-63/2/B25	TOMC3-63/2/C25	TOMC3-63/2/D25
	32A	TOMC3-63/2/B32	TOMC3-63/2/C32	TOMC3-63/2/D32
	40A	TOMC3-63/2/B40	TOMC3-63/2/C40	TOMC3-63/2/D40
	50A	TOMC3-63/2/B50	TOMC3-63/2/C50	TOMC3-63/2/D50
	63A	TOMC3-63/2/B63	TOMC3-63/2/C63	TOMC3-63/2/D63

Dimensions (mm)

