

Protection
Circuit protection

CE CB CCC TÜV Rheinland




TOMC3-63 Miniature Circuit Breaker (Curve B, C, D)

IEC 60947-2

AS/NZS 60898.1

IEC 60898-1

EN 60898-1



■ TOMC3-63 circuit breakers are multi-standard circuit breakers which combine the following functions:

- Circuit protection against short-circuit currents,
- Circuit protection against overload currents,
- Suitable for industrial isolation according to IEC/EN 60947-2, standard.

Main

Product or component type	Miniature circuit-breaker
Device application	Distribution
Poles description	1P
Number of protected poles	1
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B, C, D
Breaking capacity	4.5kA


Complementary

[Ue] rated operational voltage	110 V , 230/240V AC
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail 35mm
Colour	Grey
Endurance (O-C)	Electrical 10,000 cycles Mechanical durability 20,000 cycles

Environment

Standards	IEC 60947-2 , IEC 60898-1 , EN60898-1 , AS/NES 60898.1
IP degree of protection	IP40 for modular enclosure conforming to IEC 60529 IP20 conforming to IEC 60529
Operating altitude	2000 m
Ambient air temperature for operation	-35°C to +70°C
Ambient air temperature for storage	-40°C to +85°C

Connection

Rating	Tightening torque	Copper cables	
		Rigid	Flexible or ferrule
			
1 to 25 A	2 N.m	1 to 25 mm²	1 to 16 mm²
32 to 63 A	2.5 N.m	1 to 35 mm²	1 to 25 mm²

Catalog numbers

Type	Width 9 mm modules				
1P	Rating (In)	B Curve	C Curve	D Curve	
	1A	TOMC3-63/1/B1	TOMC3-63/1/C1	TOMC3-63/1/D1	
	3A	TOMC3-63/1/B3	TOMC3-63/1/C3	TOMC3-63/1/D3	
	5A	TOMC3-63/1/B5	TOMC3-63/1/C5	TOMC3-63/1/D5	
	6A	TOMC3-63/1/B6	TOMC3-63/1/C6	TOMC3-63/1/D6	
	10A	TOMC3-63/1/B10	TOMC3-63/1/C10	TOMC3-63/1/D10	
	16A	TOMC3-63/1/B16	TOMC3-63/1/C16	TOMC3-63/1/D16	2
	20A	TOMC3-63/1/B20	TOMC3-63/1/C20	TOMC3-63/1/D20	
	25A	TOMC3-63/1/B25	TOMC3-63/1/C25	TOMC3-63/1/D25	
	32A	TOMC3-63/1/B32	TOMC3-63/1/C32	TOMC3-63/1/D32	
	40A	TOMC3-63/1/B40	TOMC3-63/1/C40	TOMC3-63/1/D40	
	50A	TOMC3-63/1/B50	TOMC3-63/1/C50	TOMC3-63/1/D50	
	63A	TOMC3-63/1/B63	TOMC3-63/1/C63	TOMC3-63/1/D63	

Dimensions (mm)

