




# TOMC7-63 Miniature Circuit Breaker (Curve B, C, D)



IEC 60947-2 AS/NZS 60898.1  
IEC 60898-1  
EN 60898-1

- TOMC7-63 circuit breakers are multi-standard circuit breakers which combine the following functions:
  - Circuit protection against short-circuit currents,
  - Circuit protection against overload currents,
  - Suitable for industrial isolation according to IEC/EN 60947-2, standard.

## Main

Product or component type	Miniature circuit-breaker
Device application	Distribution
Poles description	2P
Number of protected poles	2
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B, C, D
Breaking capacity	6kA

## Complementary


[Ue] rated operational voltage	230V/240V, 380V/415V AC	
Control type	Toggle	
Local signalling	ON/OFF indication	
Mounting mode	Clip-on	
Mounting support	DIN rail 35mm	
Colour	Grey	
Endurance (O-C)	Electrical	10,000 cycles
	Mechanical durability	20,000 cycles

## Environment

Standards	IEC 60947-2, IEC 60898-1, EN60898-1, AS/NES 60898.1
IP degree of protection	IP40 for modular enclosure conforming to IEC 60529
	IP20 conforming to IEC 60529
Operating altitude	2000 m
Ambient air temperature for operation	-35°C to +70°C
Ambient air temperature for storage	-40°C to +85°C


## Connection

Rating	Tightening torque	Copper cables	
		Rigid	Flexible or ferrule

1 to 25 A	2 N.m	1 to 25 mm <sup>2</sup>	1 to 16 mm <sup>2</sup>
32 to 63 A	2.5 N.m	1 to 35 mm <sup>2</sup>	1 to 25 mm <sup>2</sup>

## Catalog numbers

Type	Rating (In)	B Curve	C Curve	D Curve	Width 9 mm modules
	1A	TOMC7-63/2/B1	TOMC7-63/2/C1	TOMC7-63/2/D1	4
	3A	TOMC7-63/2/B3	TOMC7-63/2/C3	TOMC7-63/2/D3	
	5A	TOMC7-63/2/B5	TOMC7-63/2/C5	TOMC7-63/2/D5	
	6A	TOMC7-63/2/B6	TOMC7-63/2/C6	TOMC7-63/2/D6	
	10A	TOMC7-63/2/B10	TOMC7-63/2/C10	TOMC7-63/2/D10	
	16A	TOMC7-63/2/B16	TOMC7-63/2/C16	TOMC7-63/2/D16	
	20A	TOMC7-63/2/B20	TOMC7-63/2/C20	TOMC7-63/2/D20	
	25A	TOMC7-63/2/B25	TOMC7-63/2/C25	TOMC7-63/2/D25	
	32A	TOMC7-63/2/B32	TOMC7-63/2/C32	TOMC7-63/2/D32	
	40A	TOMC7-63/2/B40	TOMC7-63/2/C40	TOMC7-63/2/D40	
	50A	TOMC7-63/2/B50	TOMC7-63/2/C50	TOMC7-63/2/D50	
	63A	TOMC7-63/2/B63	TOMC7-63/2/C63	TOMC7-63/2/D63	

## Dimensions (mm)

