


Protection  
Circuit protection

CE CB CCC TÜV Rheinland



## TOMC3-63 Miniature Circuit Breaker (Curve B, C, D)



IEC 60947-2

AS/NZS 60898.1

IEC 60898-1

EN 60898-1

■ TOMC3-63 circuit breakers are multi-standard circuit breakers which combine the following functions:

- Circuit protection against short-circuit currents,
- Circuit protection against overload currents,
- Suitable for industrial isolation according to IEC/EN 60947-2, standard.

### Main

Product or component type	Miniature circuit-breaker
Device application	Distribution
Poles description	4P
Number of protected poles	4
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	B, C, D
Breaking capacity	4.5kA


### Complementary

[Ue] rated operational voltage	380V/415V AC
Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	DIN rail 35mm
Colour	Grey
Endurance (O-C)	Electrical 10,000 cycles Mechanical durability 20,000 cycles

### Environment

Standards	IEC 60947-2 , IEC 60898-1 , EN60898-1 , AS/NES 60898.1
IP degree of protection	IP40 for modular enclosure conforming to IEC 60529 IP20 conforming to IEC 60529
Operating altitude	2000 m
Ambient air temperature for operation	-35°C to +70°C
Ambient air temperature for storage	-40°C to +85°C

## Connection

Rating	Tightening torque	Copper cables	
		Rigid	Flexible or ferrule
			
1 to 25 A	2 N.m	1 to 25 mm <sup>2</sup>	1 to 16 mm <sup>2</sup>
32 to 63 A	2.5 N.m	1 to 35 mm <sup>2</sup>	1 to 25 mm <sup>2</sup>

## Catalog numbers

Type	Rating (In)	B Curve	C Curve	D Curve	Width 9 mm modules
4P	1A	TOMC3-63/4/B1	TOMC3-63/4/C1	TOMC3-63/4/D1	
	3A	TOMC3-63/4/B3	TOMC3-63/4/C3	TOMC3-63/4/D3	
	5A	TOMC3-63/4/B5	TOMC3-63/4/C5	TOMC3-63/4/D5	
	6A	TOMC3-63/4/B6	TOMC3-63/4/C6	TOMC3-63/4/D6	
	10A	TOMC3-63/4/B10	TOMC3-63/4/C10	TOMC3-63/4/D10	
	16A	TOMC3-63/4/B16	TOMC3-63/4/C16	TOMC3-63/4/D16	8
	20A	TOMC3-63/4/B20	TOMC3-63/4/C20	TOMC3-63/4/D20	
	25A	TOMC3-63/4/B25	TOMC3-63/4/C25	TOMC3-63/4/D25	
	32A	TOMC3-63/4/B32	TOMC3-63/4/C32	TOMC3-63/4/D32	
	40A	TOMC3-63/4/B40	TOMC3-63/4/C40	TOMC3-63/4/D40	
	50A	TOMC3-63/4/B50	TOMC3-63/4/C50	TOMC3-63/4/D50	
	63A	TOMC3-63/4/B63	TOMC3-63/4/C63	TOMC3-63/4/D63	

## Dimensions (mm)

